

MATERIAL SAFETY DATA SHEET

PREMIER COMPANIES, INC.
10811 ALBURY
HOUSTON, TEXAS 77096

Emergency Telephone:
(800) 206-4254
Date Prepared: 5/20/08

SECTION I

Product Identity (Name / Number)	Lemon Oil Furniture Polish - High Gloss / 9731 H. G.
Chemical Family	Solvent Cleaner. Combustible liquids, n.o.s. (contains Petroleum distillates), Combustible liquid, NA1993, PGIII.

SECTION II - Hazardous Ingredients

Hazardous Components	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Petroleum Distillate	400 ppm	400 ppm		Proprietary

SECTION III - Physical & Chemical Characteristics

Boiling Point	475 - 610 °F	Specific Gravity	0.8
Vapor Pressure (mm Hg)	Less than 0.01 Lb.	Melting Point	N/A
pH	N/A	Evaporation Rate (Ethyl Ether=1)	Estimated Slower
Solubility in Water	Negligible	Appearance / Odor	Clear Liquid/Lemon

SECTION IV - Fire & Explosion Hazard Data

Flammable Limits (Explosive Limit)	Upper: 6	Lower: 0.7
Flash Point (Method Used)	Tag Closed Cup 260°F	
Extinguishing Media	Water fog, foam, dry chemical or carbon dioxide.	
Special Fire Fighting Procedures	Product is combustible. Clear fire area of unprotected personnel. Do not enter confined area without full bunker gear including positive pressure self-contained breathing apparatus.	
Unusual Fire and Explosion Hazards	Never use welding or cutting torch on or near containers (even when empty) because product can ignite.	

SECTION V - Reactivity Data

Stability:	Unstable	<input checked="" type="checkbox"/> Stable
Hazardous Polymerization:	<input checked="" type="checkbox"/> Will Not Occur	<input type="checkbox"/> May Occur
Conditions To Avoid	Avoid heat, sparks, flame and contact with strong oxidizing agents.	
Incompatibility (Materials to Avoid)	Avoid strong oxidizing agents, do not store in aluminum.	
Hazardous Decomposition or Byproducts	Carbon monoxide, carbon dioxide and unidentified organic compounds may be formed during combustion.	

SECTION VI(a) - Health Hazard Data

Inhalation	Breathing mists may cause headache and nasal and respiratory irritation. Overexposure may cause nausea, drowsiness, CNS depression, convulsions and loss of consciousness.
Eye	Will cause irritation.
Skin	May be irritating. Prolonged overexposure may cause dermatitis.
Ingestion	Same symptoms as inhalation may be experienced.

Reported As Potential Carcinogen or Carcinogen

	International Agency for Research on Cancer	X	Not Applicable
	National Toxicology Program		OSHA

SECTION VI(b) - First Aid Procedures

Inhalation	Remove victim to fresh air. If breathing is difficult, provide oxygen. If not breathing, perform artificial respiration. Get medical attention.
Eye	Immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention.
Skin	Remove contaminated clothing. Wash thoroughly with water and soap for at least 15 minutes. Get medical attention.
Ingestion	DO NOT induce vomiting. If victim is conscious and alert, give large quantities of water. Get medical attention.

SECTION VI(c) - Employee Protection

Respiratory Protection (Utilize NIOSH approved respirators. Refer to manufacturers protection factors and OSHA standard 1910.134 as a guideline.) If TLV of product is exceeded, use NIOSH approved respirator, fully enclosed.

SPECIAL PROTECTION INFORMATION:

EYE	Chemical safety goggles or face shield as appropriate.
SKIN	Chemical resistant gloves required, nitrile, neoprene or other material resistant to distillate suggested.
VENTILATION	Provide sufficient mechanical ventilation to maintain exposure below TLV's.
SPECIAL PROTECTION	Impervious clothing and boots may be worn to prevent skin contact. Showers and eyewash facilities should be in close proximity.

SECTION VII - Special Precautions

Handling and Storage	Store in cool, dry area. Avoid heat, sparks, flame and contact with strong oxidizing agents. Open containers very slowly, allowing any gas build up to be released gradually.
Other Precautions	Empty containers retain product residues. Vapors are combustible.

SECTION VIII - Environmental Protection

Spills / Releases	Notify emergency response personnel. Evacuate area and remove ignition sources. Build dike to contain flow. Remove free liquid, do not flush to sewer or open water. Pick up with inert absorbent and place in closed container for disposal.
Waste Disposal Method	Dispose of in accordance with all local, state and federal regulations.

DISCLAIMER

The information contained herein is based upon data available to us and reflects our best professional judgment. Since it is impossible to anticipate the conditions under which our products may be used, we cannot guarantee that the recommendations will be adequate for all individuals and situations. Each user of this product should determine the suitability of the product for his particular purpose and should comply with all federal, state and local regulations. Our goal is to manufacture products with zero or minimal hazards. Our products are improved daily as up-to-date information and research is received from our suppliers to use products with less or no hazards. Please feel free to contact us for current information.